

Übersicht der Belastbarkeiten



Belastbarkeiten der Tragrollen in ca. kg pro Tragrolle

| Mantellänge mm | Rohr 40x1,5 | Rohr 50x1,5 | Rohr 60x2,0 | Rohr 80x2,0 | Rohr 80x3,0 | Rohr 89x3,25 | Rohr 108x3,6 |
|-------------------|------------------|-------------------|-------------------|-------------------|----------------|-----------------|-----------------|
| | Achse 8/10/12 | Achse 10/12/15 | Achse 12/15/17 | Achse 15/17/20 | Achse 17/20 | Achse 20/25 | Achse 20/25 |
| 100 | 105 | 105 | 200 | 225 | 495 | 495 | 495 |
| 200 | 105 | 105 | 200 | 225 | 495 | 495 | 495 |
| 300 | 105 | 105 | 200 | 225 | 495 | 495 | 495 |
| 400 | 75 | 105 | 200 | 225 | 495 | 495 | 495 |
| 500 | 60 | 95 | 200 | 225 | 495 | 495 | 495 |
| 600 | 45 | 75 | 160 | 225 | 380 | 495 | 495 |
| 700 | 40 | 60 | 125 | 225 | 330 | 420 | 495 |
| 800 | 30 | 60 | 100 | 200 | 288 | 375 | 495 |
| 900 | 30 | 50 | 90 | 175 | 247 | 330 | 495 |
| 1000 | 20 | 45 | 80 | 165 | 233 | 300 | 495 |
| 1100 | | 45 | 75 | 150 | 220 | 270 | 450 |
| 1200 | | | 65 | 135 | 200 | 245 | 420 |
| 1300 | | | | 125 | 180 | 220 | 390 |
| 1400 | | | | | 172 | 200 | 365 |
| 1500 | | | | | 165 | 180 | 340 |
| 1600 | | | | | 150 | 160 | 310 |
| 1700 | | | | | 130 | 140 | 280 |
| 1800 | | | | | 120 | 130 | 260 |
| 1900 | | | | | 110 | 120 | 240 |
| 2000 | | | | | 90 | 90 | 200 |
| 2100 | | | | | 70 | 70 | 170 |
| 2200 | | | | | | 40 | 145 |
| 2300 | | | | | | | 110 |
| 2400 | | | | | | | 90 |
| 2500 | | | | | | | 75 |